

CATALYTIC HARD WATER CONDITIONERS

ADDITIVE & MAINTENANCE FREE SCALE PREVENTION WITHOUT THE USE OF POWER OR MAGNETS

NaturalSof provides an industry proven catalytic solution for scale prevention as an alternative to conventional ion exchange systems. The NaturalSof unit does not soften water in the traditional sense of removing calcium and replacing it with sodium. NaturalSof does not add anything to your water and does not remove anything either. It uses the properties of calcium carbonate (limescale) to our advantage by creating a soft non-bonding limescale crystal of which, the majority ends up in the drain.

The NaturalSof consists of a non-sacrificial lead free catalytic core made from a special alloy housed within a non-reactive stainless steel (304) tube. The use of di-electric fittings is not necessary when Always install a NaturalSof (NS05) on any hot water recirculating pumps located in the house or business.



FEATURES

No Maintenance for 10-15 years

Chemical Free and Environmentally Friendly

No Waste Water

No Drain Required

No Power Requirement

Uninterrupted Water Flow

No Magnets

Product Life Expectancy is 10-15 Years

SELECTION GUIDANCE

A home with 3.5 bathrooms or less will always use a NS1. A home with 4 bathrooms or more and 5 people or more will use a NS6. Never oversize. The model number indicates the minimum average gpm needed to consistently activate treatment. The NS6 needs 6 gpm consistently to activate treatment, which most homes rarely if ever reach. Installation between a well pump and pressure tank requires a NS6 no matter the number of bathrooms and people. Always remember to install a NS05 on any hot water recirculating pumps.

	NS05	NS1	NS6
Length (in)	10"	11.5"	12 5/8"
Weight (lbs)	0.44	2.2	3.2
Connection	3/8" NPT	1" NPT	1" NPT
Min Flow Req (gpm)	0.5	1	6
Max Flow @ 50 psi (gpm)	5	10	16

Contact Us:

1855 Lockeway Drive | Suite 506 | Alpharetta, GA 30004

Email: info@NaturalSof.com | www.NaturalSof.com

Phone/Fax: (844) 966 7225



NSF/ANSI
61 & 372

